


**Subject**
**OB25136C Demo Board Manual**

Board Model: CH5V2.4A 25136C

Doc. No.: OB\_DOC\_DBM\_25136C01


**Key features:**

- Standby power less than 75mW@264Vac
- Precise CV/CC regulation
- Primary-side sensing and regulation without TL431 and opto-coupler
- Cost effective and simplified system design
- Average efficiency meet DOE/COC
- Integrated BJT Switch
- PSR+ Synchronous rectification for high efficiency
- Audio noised free operation
- Meet EN55022 EMI

**Schematic**


## Performance Evaluation

This session presents the test results of OB25136C module up to date. Results on inrush current and safety test are not included and will be added when they become available.

Overall, the module meets design specifications. All data was measured at the end of 1.2m, 22 AWG output cable.

### Performance Highlights

- Standby power less than 75mW@264V
- Precise CV/CC regulation
- The average efficiency meet DOE Level 6/COC
- EMI passed EN55022 and FCC15 Class B test with more than 6dB margin

### System Electrical Specification

Description	Symbol	Min	Typ.	Max	Units	Comment
<b>Input Section</b>						
Input Voltage	V <sub>IN</sub>	90		264	V	2 Wire
Line Frequency	f <sub>LINE</sub>	47	50/60	63	Hz	
Standby Power				75	mW	230V
<b>Output characteristics</b>						
CV Section	Output Voltage	V <sub>OUT_CV</sub>	4.75		V	
	Output Current	I <sub>OUT_CV</sub>	0	2.88	A	
CC Section	Output Voltage	V <sub>OUT_CC</sub>	3.0		V	
	Output Current	I <sub>OUT_CC</sub>	2.64	2.88	A	
Ripple & Noise	V <sub>RIPPLE</sub>			80	mV <sub>P-P</sub>	
Continuous Output Power	P <sub>OUT</sub>		12W			
Over Current Protection	I <sub>OUT_MAX</sub>			3.12	A	
Active Mode Efficiency	η	80.30/ 71.00			%	Measured at Line End, V <sub>IN</sub> =115V/230V
<b>Time sequence</b>						
Turn on delay time				2	s	
<b>Environmental</b>						
Conducted/Radiation EMI	Meets EN55022B\FCC 15					
Safety	Meets IEC950,UL1950,Class II					
ESD		8/15			kV	

### Test Equipments

Item	Vender	Module
AC Source	WEST	WEW1010
Digital Power Meter	YOKOGAWA	WT210
Electrical Load	Chroma	63030
Oscilloscope	LeCroy	WS424
Multimeter	VICTORY	VC9807A

## 1. Input Characteristics

### 1.1 Standby power

Table. 1 Standby power

Input voltage	Pin(mW)	Vo(V)	Specification	Test result
90V/60HZ	30	4.998	<75mW	Pass
115V/60HZ	32	5.000		
230V/50HZ	50	5.003		
264V/50HZ	62	5.000		




Fig. 1 Standby Power vs. Input Voltage

### 1.2 Efficiency

Table. 2 Efficiency Line end with 22AWG, 1.2m (130mΩ) output line.

Input voltage	10%	25%	50%	75%	100%	25%~100% Load Aver. Eff.	Standards		Test Result
							DOE	COC	
115V/60Hz	82.97%	84.70%	83.62%	82.70%	81.40%	83.11%	79.94%	71.00% (10%Load)	Pass
230V/50Hz	81.62%	84.36%	83.87%	83.11%	81.95%	83.32%		80.30%	




Fig. 2 Efficiency vs. Percent of Rated Output Power

## 1.3I-V Curve




Fig. 3 I-V Curve

## 2. Output Characteristics

### 2.1 Line Regulation & Load Regulation

Table. 3 Line Regulation & Load Regulation

Input voltage	No load(V)	Half load(V)	Full load(V)	Specification(V)	Test result
90V/60Hz	5.003	5.024	4.967	4.75-5.25	Pass
115V/60Hz	5.002	5.021	4.983	4.75-5.25	
230V/50Hz	5.006	5.022	4.995	4.75-5.25	
264V/50Hz	5.009	5.020	4.994	4.75-5.25	
Line Regulation	$\pm 0.28\%$			$<\pm 2\%$	Pass
Load Regulation	$\pm 0.57\%$			$<\pm 5\%$	Pass

### 2.2 Ripple & Noise

Table. 4 Ripple & Noise

Input voltage	R&N (mV)		
	No load	Full load	Remark
90V/60Hz	14mV	77mV	Fig. 4,5
115V/60Hz	17mV	69mV	
230V/50Hz	19mV	63mV	
264V/50Hz	19mV	61mV	Fig. 6,7

Note: Ripple& noise was measured at line end with probe cap and ground clip. Measurement bandwidth was limited to 20MHz.




Fig. 4 Measured ripple&amp; noise waveform@90V/60Hz, no load




Fig. 5 Measured ripple&amp; noise waveform@90V/60Hz, full load




Fig. 6 Measured ripple&amp; noise waveform@264V/50Hz, no load




Fig. 7 Measured ripple&amp; noise waveform@264V/50Hz, full load

## 2.3 Dynamic Test

A dynamic loading with low load lasting for 50ms/20ms and high load lasting for 50ms/20ms is added to output. The high load is 1.2A and the low load is 0A. The ramp is set at  $0.125\text{A}/\mu\text{s}$  at transient. Measurement was taken at line end (Same as R&N measurement)

Table. 5 Output voltage under dynamic test(1.2A lasting for 50ms,0A lasting for 50ms)

Input	Vomin-Vomax(v)	Remark
90V/60Hz	4.74-5.64	
115V/60Hz	4.74-5.64	
230V/50Hz	4.71-5.61	
264V/50Hz	4.74-5.61	


(1.2A lasting for 20ms,0A lasting for 20ms)

Input	Vomin-Vomax(v)	Remark
90V/60Hz	4.81-5.61	
115V/60Hz	4.78-5.61	
230V/50Hz	4.81-5.64	
264V/50Hz	4.81-5.64	


### 3. EMI Test

The Power supply passed EN55022 Class B EMI requirement with more than 6dB margin

#### 3.1 Conducted EMI Test



#### 3.2 Radiation EMI Test



## Disclaimer

On-Bright Electronics reserves the right to make corrections, modifications, enhancements, improvements, and other changes to its documents, products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

This document is under copy right protection. None of any part of document could be reproduced, modified without prior written approval from On-Bright Electronics.