


Subject
OB2632P+OB2613 Demo Board Manual


Board Model: PD30W OB2632P 1831
 Doc. No.: OB_DOC_DBM_2632P+261303



Key features:

- Support Power Delivery 3.0 Protocol@ Include PPS
- Output voltage: 5V/9V/12V/15V/20V
- Output current: 3A/3A/2.5A/2A/1.5A
- Standby power less than 75mW
- Average efficiency meet COC V tier2
- Comprehensive protection coverage such as SCP、OCP、OLP、OVP、OTP
- High precision OCP performance
- Programmable cable drop compensation
- Meet EN55022 Class B EMI

Schematic



Performance Evaluation

1. Input Characteristics

1.1 Input current and Standby power

The module was tested at different input voltages (from 90Vac to 264Vac)

Table 1 Input current at full load

Input Voltage	90V/60Hz	115V/60Hz	230V/50Hz	264V/50Hz
Input Current(A)	0.64	0.55	0.36	0.35

Table 2 Standby power at no load

Input voltage	Pin(mW)	Vo(V)	Specification	Test result
90Vac/60HZ	28	4.97	<75mW	Pass
115Vac/60HZ	29	4.97		
230Vac/50HZ	58	4.97		
264Vac/50HZ	70	4.97		

1.2 Efficiency

Table 3 Efficiency @PCB End

5V3A								
	100%	75%	50%	25%	AVE	CoC Req	10%	CoC Req
115Vac	86.46	87.64	88.65	88.59	87.84	81.84%	84.43	72.48%
230Vac	84.26	85.48	87.2	84.75	85.42		80.53	

9V3A								
	100%	75%	50%	25%	AVE	CoC Req	10%	CoC Req
115Vac	88.92	89.43	89.44	90.01	89.45	87.30%	87.09%	77.30%
230Vac	88.17	87.79	89.33	87.8	88.27		84.76%	

12V2.5A								
	100%	75%	50%	25%	AVE	CoC Req	10%	CoC Req
115Vac	89.82	89.94	90.98	89.77	90.13	87.70%	86.55%	77.70%
230Vac	89.22	90.02	89.73	87.77	89.19		83.75%	

15V2A								
	100%	75%	50%	25%	AVE	CoC Req	10%	CoC Req
115Vac	90.11	89.99	90.95	89.07	90.03	87.70%	85.13%	77.7%
230Vac	91.43	90.74	89.56	87.28	89.75		82.76%	

20V1.5A								
	100%	75%	50%	25%	AVE	CoC Req	10%	CoC Req
115Vac	90.02	91.19	90.1	87.5	89.7	87.70%	84.43%	77.7%
230Vac	91.41	90.38	88.94	86.28	89.25		80.53%	

2. Output Characteristics

2.1 Line Regulation & Load Regulation

All data was measurement at @100mR CABLE end

Table 4 Line Regulation & Load Regulation

Input voltage	No load	Half load	Full load	Specification	Output Voltage
90Vac/60HZ	4.991	4.948	4.932		5V
115Vac/60HZ	4.99	4.949	4.932		
230Vac/50HZ	4.98	4.949	4.932		
264Vac/50HZ	4.986	4.949	4.932		
Line Regulation	0.22%			<2%	
Load Regulation	1.2%			<5%	

Input voltage	No load	Half load	Full load	Specification	Output Voltage
90Vac/60HZ	8.98	8.886	8.793		9V
115Vac/60HZ	8.98	8.88	8.793		
230Vac/50HZ	8.98	8.88	8.793		
264Vac/50HZ	8.973	8.878	8.789		
Line Regulation	0.1%			<2%	
Load Regulation	2.1%			<5%	

Input voltage	No load	Half load	Full load	Specification	Output Voltage
90Vac/60HZ	11.981	11.897	11.821		12V
115Vac/60HZ	11.98	11.896	11.82		
230Vac/50HZ	11.981	11.896	11.82		
264Vac/50HZ	11.98	11.896	11.821		
Line Regulation	0.03%			<2%	
Load Regulation	1.6%			<5%	

Input voltage	No load	Half load	Full load	Specification	Output Voltage
90Vac/60HZ	14.976	14.91	14.85		15V
115Vac/60HZ	14.976	14.91	14.85		
230Vac/50HZ	14.975	14.91	14.85		
264Vac/50HZ	14.976	14.91	14.848		
Line Regulation	0.02%			<2%	
Load Regulation	0.85%			<5%	

Input voltage	No load	Half load	Full load	Specification	Output Voltage
90Vac/60HZ	19.97	19.92	19.876		20V
115Vac/60HZ	19.97	19.92	19.877		
230Vac/50HZ	19.972	19.923	19.879		
264Vac/50HZ	19.973	19.923	19.88		
Line Regulation	0.02%			<2%	
Load Regulation	0.7%			<5%	

2.2 Ripple & Noise

All data was measurement at @100mR CABLE end

Table 5 Ripple & Noise

Input voltage	5V R&N (mV)		Remark
	No load	Full load	
90Vac/60HZ	50.6mv	62.1mv	
264Vac/50HZ	60.8mv	49.3mv	

Input voltage	9V R&N (mV)		Remark
	No load	Full load	
90Vac/60HZ	55.7mv	83.8mv	
264Vac/50HZ	67.8mv	59.5mv	

Input voltage	12V R&N (mV)		Remark
	No load	Full load	
90Vac/60HZ	52.5mv	87mv	
264Vac/50HZ	60.8mv	65.5mv	

Input voltage	15V R&N (mV)		Remark
	No load	Full load	
90Vac/60HZ	48mv	121mv	
264Vac/50HZ	48mv	73mv	

Input voltage	20V R&N (mV)		Remark
	No load	Full load	
90Vac/60HZ	43mv	80mv	
264Vac/50HZ	49.5mv	64.6mv	

Note: Ripple& noise was measured at DC cord end without probe cap and ground clip. Measurement bandwidth was limited to 20MHZ.

2.3 Dynamic Test

A dynamic loading with low set at 10% full load lasting for 10mS and high set at 90% full load lasting for 10mS is added to output. The ramp is set at 0.25A/uS at transient.

All data was measurement at @100mR CABLE end.

Table 6 Output voltage under dynamic test

Input voltage	5V Output voltage (mV)	Waveform
90V/60HZ	±376	Fig.15-16
264V/50HZ	±376	

Input voltage	9V Output voltage (mV)	Waveform
90V/60HZ	±360	
264V/50HZ	±352	

Input voltage	12V Output voltage (mV)	Waveform
90V/60HZ	±320	
264V/50HZ	±320	

Input voltage	15V Output voltage (mV)	Waveform
90V/60HZ	±272	
264V/50HZ	±264	

Input voltage	20V Output voltage (mV)	Waveform
90V/60HZ	±256	Fig.17-18
264V/50HZ	±240	

Dynamic waveform




Fig. 1 Dynamic waveform @90Vac input




Fig. 2 Dynamic waveform @264Vac input




Fig. 3 Dynamic waveform @90Vac input





Fig. 4 Dynamic waveform @264Vac input


3. EMI Test

The Power supply passed EN55022 Class B & FCC class B EMI requirement with more than 6dB margin tested with shield.

3.1 Conducted EMI Test




Site : Audix(Shanghai) Shielded1
 Condition : EN55022 CLASS B (QP) ESH2-25-2018 LINE
 Project No. :
 Applicant :
 EUT : OB2632P
 M/N : 20V 1.5A
 S/N :
 Power Supply : 230V/50Hz
 Ambient : 22°C 46%RH
 Test line : L
 Test Mode :
 Test Engineer : Kevin
 Memo :




Site : Audix(Shanghai) Shielded1
 Condition : EN55022 CLASS B (AV) ESH2-25-2018 LINE
 Project No. :
 Applicant :
 EUT : OB2632P
 M/N : 20V 1.5A
 S/N :
 Power Supply : 230V/50Hz
 Ambient : 22°C 46%RH
 Test line : L
 Test Mode :
 Test Engineer : Kevin
 Memo :

3.2 Radiation EMI Test



Site : Audix(Shanghai) Chamber3
 Condition : EN 55022 CLASS B VERTICAL
 Project No. :
 Applicant :
 EUT : OB2632P
 M/N : 20V 1.5A
 S/N :
 Power Supply : 230V/50Hz
 Ambient : 22°C 60%RH
 Test Mode :
 Test Engineer: Keith
 Memo :



Site : Audix(Shanghai) Chamber3
 Condition : EN 55022 CLASS B HORIZONTAL
 Project No. :
 Applicant :
 EUT : OB2632P
 M/N : 20V 1.5A
 S/N :
 Power Supply : 230V/50Hz
 Ambient : 22°C 60%RH
 Test Mode :
 Test Engineer: Keith
 Memo :

4. PD Specification Test

4.1 Vbus Change Test

Vbus changing test between 5V/9V/12V/15V/20V under No load/Full load conditions



Fig. 5 Vbus Changing Test @no load



Fig. 6 Vbus Changing Test @full load

4.2 Negative Voltage Transitions

Vbus changing test from 20V to 5V @No load/Full load. The transition time is 167ms (spec: <275ms)




Fig. 7 Vbus Change From 20V to 5V @no load




Fig. 8 Vbus Change From 20V to 5V @full load

4.3 Positive Voltage Transitions

Vbus changing test from 5V to 20V @No load/Full load. The transition time is 140ms (spec: <275ms)




Fig. 9 Vbus Change From 5V to 20V @no load




Fig. 10 Vbus Change From 5V to 20V @full load

4.4 Response to Hard Resets

When responding to hard reset, the time of $t_{Safe5V}/t_{Safe0V}/t_{SrcRecover}/t_{SrcTurnon}$ are strict following PD spec.



Fig. 11 Hard Reset $t_{0-tSafe5V}$ (spec: <275ms)




Fig. 12 Hard Reset $t_{0-tSafe0V}$ (spec: <650ms)




Fig. 13 Hard Reset $t_{SrcRecover}$ (660ms<spec<1s)




Fig. 14 Hard Reset $t_{SrcTurnon}$ (spec: <275ms)

Disclaimer

On-Bright Electronics reserves the right to make corrections, modifications, enhancements, improvements, and other changes to its documents, products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. This document is under copy right protection. None of any part of document could be reproduced, modified without prior written approval from On-Bright Electronics.